



NITROGEN PURGE KIT

Part No: RC1NIPK

This purge kit provides an engineered solution for purging easily and effectively using refillable cylinders. The kit comprises means to regulate flow to litres per minute, purge tools to allow for a quick and easy positive seal for many different pipe dimensions and a dedicated 3 metre hose. The kit allows you to purge at a regulated flow rate and create a positive seal, which reduces the amount of gas used and limits any ingress of air during the repair.

FEATURES

- Cylinder contents gauge
- Flowmeter
- 3 m inlet gas hose
- Purge tool for 5 - 20 mm (1/4" - 3/4") pipe
- Purge tool for 20 - 29 mm (3/4" - 1 1/8") pipe
- Anodised aluminum construction
- Knurled hand grips for positive seal
- Set pressure nitrogen regulator
- Gauge protector
- Accurate flow reading

SPECIFICATIONS

Regulator	
Maximum inlet pressure	20,000 kPa
Outlet pressure	300 kPa preset
Inlet connection	Type 50
Outlet connection	5/8-18 UNF RH Male
Flowmeter	
Maximum inlet pressure	800 kPa
Outlet flow range	0 - 25 L/min
Inlet connection	5/8-18 UNF RH Female
Outlet connection	5/8-18 UNF RH Male
Hose	
Maximum inlet pressure	1,200 kPa
Inlet connection	5/8-18 UNF RH Female
Outlet connection	1/4" SAE flare Female
Purge tools	
Inlet connection	1/4" SAE flare Female

PART NO	DESCRIPTION
GEPT1	Purge tool for 5 - 20 mm (1/4" - 3/4") pipe
GEPT2	Purge tool for 20 - 29 mm (3/4" - 1 1/8") pipe
RC1SNISP	Set pressure nitrogen regulator
RCFL25	Flowmeter
GWSWIG3F	3 meter inert hose

Nitrogen Purge Kits For Disposable Cylinders



NITROGEN PURGE KIT

Part No: RDNIPK

This purge kit provides an engineered solution for purging easily and effectively using disposable cylinders. The kit comprises means to regulate flow to litres per minute, purge tools to allow for a quick and easy positive seal for many different pipe dimensions and a dedicated 3 metre hose. The kit allows you to purge at a regulated flow rate and create a positive seal, which reduces the amount of gas used and limits any ingress of air during the repair.

FEATURES

- Flow gauge L/min
- Micro inert regulator
- 3 m inlet gas hose
- Purge tool for 5 - 20 mm (1/4" - 3/4") pipe
- Purge tool for 20 - 29 mm (3/4" - 1 1/8") pipe
- Accurate flow reading
- Anodised aluminum construction
- Knurled hand grips for positive seal

SPECIFICATIONS

Regulator	
Maximum inlet pressure	13,000 kPa
Outlet flow range	0 - 8 L/min
Inlet connection	M10 x 1 Female
Outlet connection	5/8-18 UNF RH Male
Hose	
Maximum inlet pressure	1,200 kPa
Inlet connection	5/8-18 UNF RH Female
Outlet connection	1/4" SAE flare Female
Purge tools	
Inlet connection	1/4" SAE flare Male

PART NO	DESCRIPTION
GEPT1	Purge tool for 5 - 20 mm (1/4" - 3/4") pipe
GEPT2	Purge tool for 20 - 29 mm (3/4" - 1 1/8") pipe
OTMRIGP5	Nitrogen regulator
GWSWIG3F	3 meter inert hose

Brochure Number: BRO_IND_PKI_NL_V03