

REFRIGERANT FACT SHEET

R134a

CHARACTERISTICS

R134a is a commonly used refrigerant in a wide range of medium and high-temperature refrigeration and air conditioning applications.

R134a is a common component in many HFC refrigerant blends and is used in some propellant applications.

PERFORMANCE

- R134a is suitable for use in new equipment and can be used as a retrofit in some R12 and R22 applications with an oil change
- Compressors must be charged with polyolester oil (check OEM guidelines)
- Lower GWP alternatives include R1234yf, R1234ze, R513A and R450A

THERMODYNAMIC PERFORMANCE

- Comparable physical and thermodynamic properties to R12
- Reduction in capacity compared to R12
- Excellent coefficient of performance

PRODUCT PART NUMBERS

- **H134012** 12kg Cylinder
- **H134022** 22kg Cylinder
- **H134065** 65kg Cylinder
- **H134450** 450kg Cylinder

For safety, handling and storage guidelines please refer to the MSDS (available on Chemwatch)

PHYSICAL ATTRIBUTES

ODP: 0

GWP: 1430

Class/ Type: Zeotropic blend (A1)

Refrigerant Kind: HFC

Oil Type: Polyolester oil (POE) and PAG

Glide: N/A


FEATURES

- Refrigerant can be charged from either the liquid or vapour phase
- R134a is miscible with synthetic oil or lubricant and is compatible with PAG-Auto and POE oil
- Non-flammable
- Cost-effective
- Energy efficient

APPLICATIONS

Medium and high temperature applications including:

- Commercial refrigeration
- Domestic refrigeration
- Transport refrigeration
- Industrial and commercial air conditioning
- Automotive air conditioning



R134a PRESSURE TEMPERATURE CHART

C°	R134a (kPa)
-40	-47
-38	-41
-36	-35
-34	-28
-32	-21
-30	-14
-28	-5
-26	3
-24	14
-22	26
-20	39
-18	49
-16	59
-14	72
-12	86
-10	101
-8	118
-6	135
-4	153
-2	172
0	192
2	211
4	229
6	253
8	283
10	313
12	342
14	372
16	403
18	436
20	469
22	507
24	544
26	584
28	626
30	668
32	715
34	761
36	811
38	863
40	915
42	972
44	1029
46	1090
48	1153
50	1217

PHYSICAL PROPERTIES

Class/ Type	Zeotropic blend
Formula	100% R134a
Kind	HFC
Appearance	Colourless
ODP	0
GWP	1430
ASHRAE Std. 34 Safety Class	A1

Units	Physical Properties
Molecular Weight	102.03 kg/mol
Boiling Point	-26.1°C
Critical Temperature	101.1°C
Critical Pressure	46.6 bar
Critical Volume	0.00194 m³/ kg
Critical Density	515.3 kg/m³
Vapour Density at Boiling Point	367.064 kg/m³
Liquid Density at 0°C	1295.1 kg/m³



- 

Quality control
ISO9001
- 

Local
manufacture
and decanting
- 

ARCTick Reporting
- 

Access to Kirby
refrigerant
technical
library
- 

Refrigerant recovery
with zero emissions
- 

Distribution and
delivery nationally
- 

Cylinder management
at your fingertips
through the
Gas2Go app
- 

Refrigerant
sample analysis