

INTRODUCING THE ALL NEW BLACKMAX[®] VPC2S-18VDC CORDLESS VACUUM PUMP

Designed for servicing split systems, domestic and small commercial refrigeration, automotive A/C as well as sites where power supply is not available to use, this small compact 48 l/m cordless vacuum pump comes with a 6.0Ah 18v battery that will give you up to 1 hour run time and comes standard with an integrated solenoid valve to prevent oil cross contamination when battery runs out.

KEY FEATURES

- Small, lightweight and portable
- 48 l/m Capacity
- 18v 6.0Ah Li-on battery
- Up to 1 hour run time per battery
- Rated vacuum of 100 microns single stage
- Normally closed safety solenoid valve
- Valve automatically closes on low voltage
- Reinforced base provides extreme shock resistance
- Comes with 1/4"SAE and 5/16"SAE outlet fittings
- Easily accessible oil drain port
- Equipped with our exclusive oil mist free exhaust port



ACCESSORIES

VPCXB18	18V 6.0Ah Replacement Battery
VPCXBCAU	3.0Amp 2 Hour Universal Battery Charger
VPCXC	Black Metal Carry Case

VPC2S-18VDC (PICTURED)

SPECIFICATIONS

MODEL	MOTOR SIZE	CAPACITY	VACUUM	STAGE	POWER SOURCE	INTAKE FITTINGS	INLET SOLENOID
VPC2S-18VDC	1/5HP 3000rpm	48 l/m	100 micron	Single	18VDC Li-on Battery, 6.0Ah	1/4" & 5/16" SAE	Normally Closed
VPC2D-18VDC	1/5HP 3000rpm	48 l/m	20 micron	Two	18VDC Li-on Battery, 6.0Ah	1/4" & 5/16" SAE	Normally Closed



IGNITION PROOF VACUUM PUMP WITH SOLENOID

- Non sparking brushless motor with sealed start components and ignition proof ON/OFF switch
- Suits common refrigerants, HFOs, R32/R1234 series and ammonia vapours
- Normally closed solenoid for vacuum protection
- 144L/M and 288L/M models

MODEL	MICRON	L/M	H.P	SOLENIOD
VPS6DAV	10	144	1/2	Yes
VPS6DA	10	144	1/2	No
VPS12DAV	25	288	1	Yes

PREMIUM SERIES DUAL STAGE VACUUM PUMPS

- Lowest micron ratings in the industry
- Aircooled thermally protected motors
- Exclusive built-in oil-mist prevention
- Best performance to weight ratio in the industry

MODEL	MICRON	L/M	H.P
VP2DE	10	48	1/4
VP4DE	10	96	1/2
VP6DE	10	144	1/2
VP8DE	25	192	2/3
VP10DE	25	240	3/4
VP12DE	25	288	1



DUAL STAGE COMPACT SERIES

- Small compact light weight design
- 48 L/M capacity
- 15 micron vacuum rating
- 1/4 HP motor
- 1/4" SAE & 1/2" ACME fittings