



A CSW Industrials Company

PRODUCT DATA SHEET

**AC LEAK FREEZE® PRO**  
Leak Sealant & System Enhancer

**Description**

AC Leak Freeze is the ideal product for A/C unit repair and refrigeration repair. AC Leak Freeze will stop leaks of refrigerant gas in HVACR air conditioning and refrigeration systems in homes and commercial buildings. AC Leak Freeze ensures that the A/C repair or refrigeration repair permanently seals leaks. It is formulated to not harm A/C Refrigeration components.

Once applied, AC Leak Freeze will stay in your system in a suspended state indefinitely until it mixes with any refrigeration gas. At that point, it is activated by refrigerant escaping at the site of the leak, forming a chemical weld and sealing the leak. If for any reason the refrigerant must be reclaimed, AC Leak Freeze will be reclaimed with it, and will need to be reapplied with the new refrigerant.

AC Leak Freeze is compatible with all standard refrigerants. NANO leak sealant formula is reliable, safe and polymer free. Magic Frost adds an anti-friction lubricant to reduce noise/vibration so system runs smoother, more efficient. UV adds the ability for a UV light source to detect larger leaks for system assessment. Infuses into system through standard 1/4" service port using an HVAC manifold. Available in single use ready to use canisters, 1.46 oz for up to 6 ton units, 0.5 oz for mini-split units up to 2 tons or 24,000 BTUs.



**Applications**

- Revitalizes A/C & refrigeration systems by permanently sealing small, hard-to-find micro leaks
- Infuses into system through standard 1/4" service port using an HVAC Manifold
- For use in copper and aluminum coils
- Non-clogging to compressors, recovery units, Schrader valves, cap tubes, TXV valves, micro channels, evacuation equipment and gauges
- Compatible with all refrigerants
- Magic Frost formula enhances system performance to reducing compressor noise and extend compressor life
- UV formula adds the ability for a UV light source to detect larger leaks for system assessment

**Characteristics | Features**

- Single use - disposable
- Polymer free nano formula
- Safe for system
- Ready to use
- Non-flammable
- Non-Toxic
- POP packaged
- OEM Approved

**Packaging**

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
45309	.5 oz (15 mL) PRO Mini-split	12	6	.19
45308	.5 oz (15 mL) UV Mini-split	12	6	.19
45316	1.46 oz nano	12	8	.32
45317	1.46 oz nano Magic Frost	12	8	.32
45318	1.46 oz nano UV	12	8	.32

# AC LEAK FREEZE® PRO

Leak Sealant & System Enhancer

## Specifications

Flash Point SETA CC	>379° F
Color	Green (w/Magic Frost) Blue (Original) Yellow (UV)
Odor	Petroleum
Shelf Life	4 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## Precautionary Statements

Refer to Safety Data Sheet (SDS).

### KEEP OUT OF REACH OF CHILDREN

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

For additional Technical Information Call Toll Free 1-800-231-3345

## Limited Warranty



For more information on our product limited warranty, visit [RectorSeal.com](http://RectorSeal.com)

Manufactured by

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

**3255 Wyandotte St. East • Windsor, ON NBY 1E9, Canada • 519-966-4901**

**PO Box 5266 • Brendale, Qld 4500, Australia • 1300 77 2878 • [rectorseal.com.au](http://rectorseal.com.au)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2022 RectorSeal. All rights reserved. R50530-0622