

SOFT DRAWN COPPER



Freddox's R410A rated copper tube complies with soft return for pressure piping and is capable of withstanding safe working pressures in accordance with AS 4041 as referenced below.

Features

- Eliminate contamination risks with clean quality copper that is maintained through the inclusion of superior end caps
- Manufactured to AS/NZS 1571 – Copper Seamless Tube for Air-Conditioning & Refrigeration
- Tubing is identified with ink marking along its length stating brand name, conforming standard, temper, size (O.D & wall) and batch number. Example: "FREDDOX AS/NZS 1571 H 28.58 O.D x 1.83 Wall – 1113". This ensures ease of identification for quality control



TECHNICAL DATA

ITEM NO.	COPPER TUBE O.D (mm)	WALL THICKNESS (mm)	COPPER TUBE O.D (in)	SAFE WORKING PRESSURE (KPA) AT SERVICE TEMPERATURES			LENGTH (M)
				55°C	60°C	65°C	
CTSD0635-080	6.35	0.71	1/4	8862	8548	8235	30
CTSD0952-080	9.52	0.71	3/8	5699	5497	5296	18
CTSD1270-100	12.70	0.81	1/2	4823	4653	4482	18
CTSD1588-100	15.88	1.02	5/8	4859	4688	4516	18
CTSD1905-114	19.05	1.14	3/4	4508	4349	4190	18
CTSD2223-140	22.23	1.40	7/8	4760	4595	4425	18

FREDDOXSDCOPPER_1222