

SUSPENSION HANGER

Suits both M8 & M10 threaded rod

Suspension Hangers are used to support pipe work from over head positions. Suspension Hangers allow the support of both the liquid & gas lines in the one support.

The fast installation of both the Suspension Hanger and pipe work makes this a very cost effective, labour saving method.

Suspension Hanger Specifications

- Use in areas that are fire rated
- 8 microns yellow zinc plated
- Avoids the need for cable tray
- Quick and easy pipe installation
- Supplied in bags of 10

Dimensions

(Approximate pipe sizes allowing for insulation)

	JBBJ2	JBBJ3	JBBJ4
LIQUID	3/8	1/2	5/8
GAS	5/8	7/8	1 1/8



THREE EASY STEP INSTALATION

1. Fix to M8 or M10 threaded rod.



2. Install pipe work into suspension hanger.



3. Close hinged tongue into slot and bend over locking tag against threaded rod.



J.M.D. BUILDING SERVICES

P.O Box 4011, Illawong NSW 2234. Unit10, 800-812 Old Illawarra Road, Menai NSW 2234

Tel: 02 9543 8600 Fax: 02 9543 8622

E-mail: chris@jmdbuildingservices.com.au Website: www.jmdbuildingservices.com.au

ABN: 29 767 157 943