



MOTOR SPECIFICATION

MOTOR MODEL : KJA2C4704	SAMPLE NO. : K0473-8
--------------------------------	-----------------------------

MOTOR DETAILS : 240V 50Hz 0.22A 7W 1300RPM. CAPACITOR : - μF - VAC. ROTATION : CWLE

LOAD DETAILS : -

CHARACTERISTICS	TOLERANCE	240V/50Hz
HIGH	INPUT (W)	± 10% 32.9
	CURRENT (A)	± 10% 0.22
	SPEED (RPM.)	± 60 1300
	TORQUE(OZ.IN)	± 10% 6.8
	OUT PUT (W)	± 10% 7
-	INPUT (W)	- -
	CURRENT (A)	- -
	SPEED (RPM.)	- -
	TORQUE(OZ.IN)	- -
	OUT PUT (W)	- -
-	INPUT (W)	- -
	CURRENT (A)	- -
	SPEED (RPM.)	- -
	TORQUE(OZ.IN)	- -
	OUT PUT (W)	- -
-	INPUT (W)	- -
	CURRENT (A)	- -
	SPEED (RPM.)	- -
	TORQUE(OZ.IN)	- -
	OUT PUT (W)	- -
MAXIMUM TORQUE (OZ.IN.)		9.0
STARTING TORQUE (OZ.IN)		3.9
LOCK ROTOR AMPS.		0.30

VOLTAGE RANGE	240V ± 10% AT 50Hz
LIFE	SELF ALIGNING BEARING : MIN. 25000 Hrs.
INSULATION RESISTANCE	MIN 10 MΩ @ 500 VDC.
DIELECTRIC STRENGTH (HI-POT)	1.8 KV. (ONE SECOND)
PROTECTOR	THERMALLY PROTECTED RATING 130°C ± 5°C
ENCLOSURE	TOTALLY CLOSED
TEST REPORT	CONSISTS OF TORQUE,AMPS,WATTS IN,WATTS OUT,AND SPEED AT RATED,ROTATION
PACKING	WILL BE ADEQUATELY PACKED TO PROTECT MOTOR FROM SHIPPING DAMAGE.

THE INFORMATION HEREIN IS THE PROPERTY OF KULTHORN ELECTRIC CO., LTD. AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION. ANY COPYING, TRANSMITTAL OR USE BY OTHERS EXCEPT THE FOR WHICH IT IS LOANED, IS STRICTLY PROHIBITED.