



MOTOR SPECIFICATION

MOTOR MODEL : KJB2S4701	SAMPLE NO. : K0806-2
--------------------------------	-----------------------------

MOTOR DETAILS : 240V 50Hz 0.60A 28W 1350RPM CAPACITOR : - μF - VAC. ROTATION : CWLE

LOAD DETAILS : -

CHARACTERISTICS		TOLERANCE	-
HIGH	INPUT (W)	± 10%	86
	CURRENT (A)	± 10%	0.60
	SPEED (RPM.)	± 70	1350
	TORQUE(OZ.IN)	± 10%	27.8
	OUT PUT (W)	± 10%	28
-	INPUT (W)	-	-
	CURRENT (A)	-	-
	SPEED (RPM.)	-	-
	TORQUE(OZ.IN)	-	-
	OUT PUT (W)	-	-
-	INPUT (W)	-	-
	CURRENT (A)	-	-
	SPEED (RPM.)	-	-
	TORQUE(OZ.IN)	-	-
	OUT PUT (W)	-	-
-	INPUT (W)	-	-
	CURRENT (A)	-	-
	SPEED (RPM.)	-	-
	TORQUE(OZ.IN)	-	-
	OUT PUT (W)	-	-
MAXIMUM TORQUE (OZ.IN.)			37.6
STARTING TORQUE (OZ.IN)			12.7
LOCK ROTOR AMPS.			0.92

VOLTAGE RANGE	240V ± 10% AT 50Hz
LIFE	PROJECTED BEARING LIFE WITH STANDARD GREASE = 25000 Hrs. AT 70°C.
INSULATION RESISTANCE	MIN 10 MΩ @ 500 VDC.
DIELECTRIC STRENGTH (HI-POT)	1.8 KV. (ONE SECOND)
PROTECTOR	THERMALLY PROTECTED RATING 130°C ± 5°C
ENCLOSURE	TOTALLY CLOSED
TEST REPORT	CONSISTS OF TORQUE,AMPS,WATTS IN,WATTS OUT,AND SPEED AT RATED,ROTATION
PACKING	WILL BE ADEQUATELY PACKED TO PROTECT MOTOR FROM SHIPPING DAMAGE.

THE INFORMATION HEREIN IS THE PROPERTY OF KULTHORN ELECTRIC CO., LTD. AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION. ANY COPYING, TRANSMITTAL OR USE BY OTHERS EXCEPT THE FOR WHICH IT IS LOANED, IS STRICTLY PROHIBITED.