

**068U3945** **Thermostatic expansion valve, TUA, R448A**

Temperature range [°C]: -40 - 10, Pressure equalization: Internally equalized

PRODUCT DETAILS

Gross weight	0.181 Kilogram
Net weight	0.149 Kilogram
Volume	0.402 Liter
EAN	5714279000788
Approval	EAC LLC CDC TYSK UL
Body material	Stainless steel
Capillary tube length [in]	59 in
Capillary tube length [mm]	1500 mm
China RoHS compliance	Yes exceed limitations
Connection material	Bi-metal: Steel/copper
Contain batteries	No
Direction	Straightway
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a) 6(c)
Flow direction	Single-flow
Flow direction indicator	Laser engraved 1-way arrow
Fluid Group	2
Inlet connection type	Solder, ODF
Inlet size [in]	3/8 in
Max. Working Pressure [bar]	34 bar
Max. Working Pressure [psig]	500 psig
Outlet connection type	Solder, ODF
Outlet size [in]	1/2 in
Packing format	Multi pack
Parts included	Bulb strap
Parts Program name	TUA
PED category	Art. 4, par. 3
Pressure equalization	Internally equalized
Product accessories	TXV accessories
Product group	Expansion valves
Product Name Description	Thermostatic expansion valve
Quantity per packing format	24 pc
Rated cap. cond. Range N [IMP]	OS=7.2 °F tcond=100 °F tevap=40 °F tliq=98 °F

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

Rated cap. cond. Range N [SI]	OS=4K tcond=38 °C tevap=4.4 °C tliq=37 °C
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerants	R448A
SCIP dossier no.	07795324-de66-41b2-9761-afe6640e393c
SCIP dossier product name	TU/TC - Thermostatic expansion valve
Seal	No
Serviceable	TXV spare parts
Static Superheat (SS) [°C]	4 °C
Static Superheat (SS) [°F]	7.2 °F
Superheat setting	Adjustable
Temperature range [°C] [max]	10 °C
Temperature range [°C] [min]	-40 °C
Temperature range [°F] [max]	50 °F
Temperature range [°F] [min]	-40 °F
Type	TUA
UA address	UA_2L.png
UK RoHS compliance	Out of scope
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)