

Technical Specification | Mini Pumps

Mini Blanc

Part No: Deluxe FP1080 / Basic FP1077







Dimensions:

Height: 115mm Width: 182mm Depth: 55mm Weight: 0.46 kg

Power Supply:

• **Deluxe:** 220 – 240V AC < 16W • **Basic:** 220 – 240V AC < 11W

• 1PH 50/60 Hz

• 3A volt-free Alarm wires, N/C contacts rated @ 5A inductive at 220 - 240V AC

In The Box:

- Frame with AV grommets
- Pump module
- PCB module (either with socket for 'Deluxe' model or hard-wired 1m cable for 'Basic' model)
- Float
- Float retainer
- Stayclean tablet
- Filter
- Reservoir
- Cover
- Plug/1m cable assembly (for 'Deluxe' version)
- Fixing pack, containing 3 x No.8 x 25mm screws, 3 x rawl plugs and 1 x hose clamp

Other Features:

• **Deluxe:** Push-in plug • Basic: Hard-wired • Inlet i/d: 21mm

• Discharge tube: 6mm - 1/4" i/d


• Hall effect semi conductor level sensors, with high level safety

- Cleanable/replacable 70 micron internal filter
- Maximum water temperature: 40°C
- Fully potted electronics
- Thermally protected
- Continuously rated
- CE marked
- Class II appliance

Performance:

Deluxe:

- Water flow rate: 12 litres/hour at zero head
- Max. recommended head: 10m.
- 21dB(A) @ 1m



Basic:

- Water flow rate: 6 litres/hour at zero head
- Max. recommended head: 4m
- 18dB(A) @ 1m





The Mini Blanc is the latest addition to the Aspen family of mini pumps, and has been designed to give the installation flexibility, where the latest generation of A/C units are becoming

The Mini Blanc is a discreet mini pump that can be mounted directly below the wall unit.





Apex Way Hailsham East Sussex BN27 3WA T: +44 (0)1323 848842 F: +44 (0)1323 848846 sales@aspenpumps.com

www.aspenpumps.com