

COPPER SPUN FILTER DRIERS

Part Number	Capacity (gms)	Size					Tails		Comments
		Inlet	Outlet	*Outlet Cut Size	Body Dia. (mm)	Body Length (mm)	Inlet	Outlet	
XH9 Desiccant (Suitable for use with all old and new refrigerants and matching lubricants)									
120110XH9	10	1/4"ID	Capillary 2.5mm ID	–	17.5	105	–	–	Bi-directional
120110XH9TT	10	1/4"OD	1/4"ODx2	–	17.5	111	100	135	Bi-directional
120115XH9	15	1/4"ID	Capillary 2.5mm ID	–	17.5	135	–	–	Bi-directional
120115XH92	15	1/4"IDx2	1/4"ID	–	17.5	142	–	–	Bi-directional
120115XH9316	15	3/16"ID	Capillary 2.5mm ID	–	17.5	132	–	–	Bi-directional
120120XH9	20	1/4"ID	Capillary 2.5mm ID	–	24	115	–	–	Bi-directional
121025XH9R	25	3/8"ID	3/8"ID	–	24	142	–	–	Bi-directional
121415XH9	15	5/16"OD / 1/4"ID	3/16"ID	5/16"OD / 1/4"ID	17.5	134	40	55	Bi-directional
121420XH9	20	5/16"OD / 1/4"ID	5.5mm OD / 3.5mm ID	5/16"OD / 1/4"ID	24	118	45	50	Directional
121430XH9	30	5/16"ID / 1/4"ID	5.5mm OD / 3.5mm ID	5/16"OD / 1/4"ID	24	147	58	50	Directional

* Outlet cut size is the connection size after cutting the tail pipe to within 25mm of the drier body.

